

 Super Products®
SUPERSUCKER®
INDUSTRIAL VACUUM LOADER



LEAVE THE JOB SITE SPOTLESS

- High power airflow sucks up solids, liquids, sludges and slurries
- Full power extendable boom with back of cab storage
- Full opening, 6 latch tailgate with multi-position safety prop

800.837.9711 • WWW.SUPERPRODUCTSLLC.COM

SUPERSUCKER®



SPECIFICATIONS

GENERAL DIMENSIONS

- Length: 33' 7" (approx.)
- Height: 12' 8" (approx.)
- Width: 8' Body, 9' 2" with mirrors (approx.)

VACUUM SYSTEM

- 8" positive displacement vacuum system offers 5800 cfm/28" hg
- Heavy duty transfer case drive

FILTRATION SYSTEM

- Single mode filtration enables loading of wet or dry material with no changeover required
- Reverse air pulsation system continuously cleans the 60 snap-ring type, acrylic-coated filter bags
- Easy filter access on top of unit for filter bag change out; bag removal through top covers, side doors for bin cleanout
- One (1) large cyclone with large passage ways for greater airflow, greater performance and greater fuel economy

DEBRIS BODY

- 18 cu yd payload capacity
- ¼" steel construction throughout entire body and filter chambers
- Body dumping is achieved by one heavy duty, telescopic double-acting cylinder that provides a 51° dump angle.
- The body, bag houses and separator chamber hydraulically raise together, allowing for quick unloading of material
- Full opening tailgate with two lift cylinders
- The hydraulic tailgate latching system is liquid tight and prevents leakage in case of hydraulic malfunction; latches are fully adjustable

FEATURE OPTIONS

- *Stainless steel components*
- *Stainless steel debris body*
- *Rear LED work lights*
- *Sludge pump*
(Length of unit changes to 35' 7")
- *5' extendable boom with*
10' - 15' reach
(Height of unit changes to 13' 2")
- *Air Excavation Package*

MODEL OPTIONS

- *High dump unloading*
- *Arctic, designed for extreme temperatures*

* Disclaimer: Product photos may include standard and/or optional features